# **Manthorpe Building Products Product Information Sheet** CODE GRPA-1 **Flexible Pipe** 645 502 **DVAL TO FIT GRSV30/25 OR GRS** 10 interna -104-

### **Description:**

GRPA-1 Flexible Pipe is designed to provide a flexible connection between a 110mm diameter pipe outlet and a variety of extraction terminals such as the Manthorpe Hooded Slate Vent's oval spigot and other terminals with a round 110mm diameter connection.

The flexible pipe can be used to couple to a 4" soil pipe or mechanical extraction equipment and is supplied with its own metal screw clamp for simple fixing.

COLOUR	Black
PACKING DETAILS	Packed in 5s in a poly bag.
PART WEIGHT	330g
MATERIAL	LDPE
MANUFACTURING PROCESS	Blow Moulded
GEOMETRIC FREE AREA	7,500mm <sup>2</sup>

MANTHORPE BUILDING PRODUCTS LTD MANTHORPE HOUSE	TEL: 01773 303 000 FAX: 01773 303 300	DRN J.B.	Date 20.06.19	DRG No	Issue
BRITTAIN DRIVE CODNOR GATE BUSINESS PARK RIPLEY DERBYSHIRE DE5 3ND	EMAIL: mbp.care@manthorpebp.co.uk WEB www.manthorpebp.co.uk	of continuous product range	maintains a policy development of its and reserves the the specification	MBP 8332	<b>C</b> (1 of 2)

## **Manthorpe Building Products**


**Product Information Sheet** 


## **Flexible Pipe**


CODE GRPA-1

#### Fitting Instructions ... connecting to a 4 inch round spigot/pipe

Option 1	To connect end (A) to a 4 inch pipe or spigot, slide over the spigot or pipe and then tighten the jubilee clip around the overlap to secure.	
Option 2	To connect end (B) use a pipe coupler to tightly seal to both the pipe and GRPA-1 product.	
Option 3	Multiple units can be connected to achieve additional length by inserting end (B) into end (A). Push the ends firmly together until the stepped lip locates in the corresponding channel.	







Fitting Instructions connecting to a Manthorpe Hooded Slate Vent (GRSV30/25 or GRSV45)				
Step 1	Remove the jubilee clip. Then press in the sides of end (A) to form an oval.			
Step 2	Insert the pipe <b>INSIDE</b> the oval spigot on the Manthorpe Hooded Slate Vent. Push firmly together until the spigot clips engage over the ledge on the pipe.			
	NB. GRPA pipes cannot be used with the GRSV30/25R or GRSV45R Refurb Slate Vents owing to the spigot being removed.			

